ThermOmegaTech®

WASHDOWN HOSE ASSEMBLY

PREMIUM WHITE CREAMERY HOSE FOR WASHDOWN STATIONS

A premium steam rated creamery hose for steam/ water mix washdown applications in processing plants as well as food, beverage, dairy, and bakery facilities.



DESIGN FEATURES

- Alfagomma T350LL
- Steam and water rated
- High tensile textile cord reinforcement
- White EPDM tubing and cover
- Able to withstand +330°F
- Stainless steel swivel fittings
- Internal strain relief on station end
- ½" MNPT x ¾" MNPT end connections

DIMENSIONS & CAPACITIES

I.D	Nominal O.D.		Weight (per 100ft.)		Maximum Operating Pressure	Maximum Steam Pressure
	in.	mm.	lb.	kg.		
¾"	1 ¼	31	44	20	225 PSIG (15 BAR)	90 PSIG (6 BAR)

ORDERING

Part Number	Description
940-110030-025	25 ft. White Hose Assembly
940-110030-050	50 ft. White Hose Assembly
940-110030-075	75 ft. White Hose Assembly

ThermOmegaTech®, Inc.
353 Ivyland Road
Warminster, PA 18974
1-877-379-8258
www.ThermOmegaTech.com

Because of continuous improvements, ThermOmegaTech, Inc. reserves the right to change the design and specifications without notice