ThermOmegaTech®

WASHDOWN HOSE ASSEMBLY

HOT WATER HOSE FOR WASHDOWN STATIONS

Cost effective, high quality washdown hose assemblies designed to complement the HCS and HCX Water Washdown Stations. Available in Black General Purpose or White Creamery versions.





DESIGN FEATURES

- 4 ply textile reinforcement
- EPDM Tube
- White or black EPDM cover
- Brass and Zinc plated steel swivel fittings
- Strain relief coupling on station end.
- 300 PSIG max. operating pressure
- 200°F max. operating temperature
- ½" MNPT x ¾" MNPT end connections
- *Not for Steam Service*

DIMENSIONS & CAPACITIES

Type	I.D	Nominal O.D.		Weight (per 100ft.)		Maximum Operating Pressure	Maximum Operating Temperature
		in	mm	Lb	Kg		
White Creamery	3/4"	1.25	31.8	48	22	300 PSIG/20.7 BAR	200° F/93.3°C
Black General Purpose	3/4"	1.156	29.4	37	17	300 PSIG/20.7 BAR	200° F/93.3°C

ORDERING INFORMATION

Part Number	Description	Part Number	Description
940 - 000100 - 025	25 Ft. Black Hose Assembly	940 - 100100 - 025	25 Ft. White Creamery Hose Assembly
940 - 000100 - 050	50 Ft. Black Hose Assembly	940 - 100100 - 050	50 Ft. White Creamery Hose Assembly
940 - 000100 - 075	75 Ft. Black Hose Assembly	940 - 100100 - 075	75 Ft. White Creamery Hose Assembly

ThermOmegaTech®, Inc.
353 Ivyland Road
Warminster, PA 18974
1-877-379-8258
www.ThermOmegaTech.com

WASHDOWNHOSE
5/1/2020

Because of continuous improvements, ThermOmegaTech®, Inc. reserves the right to change the design and specifications without notice